2001 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 2001 *Forest Products Journal*, volume 51, are listed both by subject and by author. Reprints of most articles are available at $6 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $6 minimum charge plus $5 handling charge per order. There is a charge of $6 for a copy of the 2001 *FPJ* Subject and Author Index.

ADHESIVES/ADHESION

Influence of Splice Length on Strengths of Glued Splice OSB Joints in Tension, Y.H. Chui and C. Ni, 2:23-28 (No. 9100).

Reducing Warp and Checking in Plantation-Grown Yellow-Poplar 4 by 4's by Reversing Part Positions and Gluing in the Green Condition, R. Serrano and D. Cassens, 11/12:37-40 (No. 9231).

AIR AND WATER QUALITY

Estimated U.S. Forest and Paper Industry CO_2 Emissions Resulting From Compliance With Federal Environmental Regulations, S.C. Stratton, R.A. Miner, D.H. Word, E.H. Mannisto, and H.I. Mannisto, 5:25-31 (No. 9110).

Response Surface Methodology Study of VOCs in Plywood Press Emissions, A. Barry, R. Lépine, R. Lovell, and S. Raymond, 1:65-73 (No. 9082).

ANATOMY AND QUALITY

Growth Characteristics of Moso Bamboo in South Carolina, A.W.C. Lee and S.C. Addis, 2:88-89 (No. 9090).

Modification of the Growth Habit of the Softwood Disfiguring Fungus *Ophiostoma piceae* by Monoterpene Vapors, C. Payne, S. Woodward, and J.A. Petty, 7/8:89-92 (No. 9237).

Wood Machining Properties of White Spruce From Plantation Forests, R.E. Hernández, C. Bustos, Y. Fortin, and J. Beaulieu, 6:82-88 (No. 9140).

CHEMISTRY AND CHEMICAL MODIFICATION

Physical, Mechanical, and Chemical Properties of Steamed Beech Wood, N. Yilgor, O. Unsal, and S.N. Kartal, 11/12:89-93 (No. 9183).

Seasonal Variation of Southern Pine Terpenes, T.E. Conners, L.L. Ingram, W. Su, H. Yan, S. Banerjee, A.T. Dalton, M.C. Templeton, and S.V. Diehl, 6:89-94 (No. 9029).

COMPOSITES AND ENGINEERED PRODUCTS

Bending Strength of Gusset-Plate Joints Constructed of Wood Composites, J. Zhang, D.E. Lyon, F. Quin, and B. Tackett, 5:40-44 (No. 9135).

Flake Orientation Effects on Physical and Mechanical Properties of Sweetgum Flakeboard, T.F. Shupe, C.Y. Hse, and E.W. Price, 9:38-43 (No. 9138).

The Influence of Furnish Moisture Content and Press Closure Rate on the Formation of the Vertical Density Profile in Oriented Strandboard, C.K. Andrews, P.M. Winistorfer, and R.M. Bennett, 5:32-39 (No. 8930).

Influence of Splice Length on Strengths of Glued Splice OSB Joints in Tension, Y.H. Chui and C. Ni, 2:23-28 (No. 9100).

Laboratory Decay Resistance of Woodfiber/Thermoplastic Composites, S. Verhey, P. Laks, and D. Richter, 9:44-49 (No. 9160).

Mechanical Properties of Composites Made With Wood Fiber and Recycled Tire Rubber, X.M. Song and J.-Y. Hwang, 5:45-51 (No. 8549).

Medium Density Fiberboard Made From *Eucalyptus saligna*, A.M. Krzysik, J.H. Muehl, J.A. Youngquist, and F.S. Franca, 10:47-50 (No. 9175).

A Model of the Effect of Strand Length and Strand Thickness on the Strength Properties of Oriented Wood Composites, D. Barnes, 2:36-46 (No. 9066).

Particleboard Made From Remediated CCA-Treated Wood: Evaluation of Panel Properties, C.A. Clausen, S.N. Kartal, and J. Muehl, 7/8:61-64 (No. 9159).

Performance of Fasteners in Wood Flour-Thermoplastic Composite Panels, R.H. Falk, D.J. Vos, S.M. Cramer, and B.W. English, 1:55-61 (No. 9080).

Permanent Bracing Design for MPC Wood Roof Truss Webs and Chords, C.R. Underwood, F.E. Woeste, J.D. Dolan, and S.M. Holzer, 7/8:73-81 (No. 9128).

Technical Feasibility of Structural Flakeboard Made From Mixed Hardwoods and Cypress From Northern Florida, T.F. Shupe, C.Y. Hse, and E.W. Price, 1:62-64 (No. 9085).

DETERIORATION/DEGRADATION AND PRESERVATION

Application of Radio-Frequency Heating to Utility Poles. Part 2. Accelerated Fixation of Chromated Copper Arsenate, F. Fang, J.N.R. Ruddick, and S. Avramidis, 9:53-58 (No. 9141).

Application of Radio-Frequency Heating to Utility Poles. Part 3. The Use of RF Heating to Eradicate Decay Fungi in Pole Material, F. Fang, J.N.R. Ruddick, and S. Avramidis, 11/12:51-55 (No. 9147).

Arrest of Fungal Pre-Infections in Raw Logs and Freshly Sawn Lumber of Radiata Pine Using Sentry®, B. Kreber, M. Kimberley, D. Eden, C. Chittenden, J. Van der Waals, R. Wakeling, and I. Dorsey, 10:66-72 (No. 9173).

Control of Graystain in Yellow-Poplar Lumber by Log Fumigation With Sulfuryl Fluoride, E.L. Schmidt, D.L. Cassens, and B.A. Jordan, 9:50-52 (No. 9149).

The Durability of Yellow-Poplar and American Beech Treated With Chromated Copper Arsenate, J.J. Slahor, C.C. Hassler, and B. Dawson-Andoh, 4:62-66 (No. 9154).

Durability of Yellow-Poplar and American Beech Treated With Creosote and Borate, J.J. Slahor, H.M. Barnes, B. Dawson-Andoh, T.L. Amburgey, and C.C. Hassler, 7/8:51-55 (No. 9248).

The Durability of Yellow-Poplar and Red Maple Treated With ACQ-B, J.J. Slahor, C.C. Hassler, and B. Dawson-Andoh, 9:59-62 (No. 9250).

Effect of Gaff Design on Linemen's Perception of the Climbability of Red Pine Utility Poles of Pre-Selected Wood Hardness, R. Gilbert, A. Besner, Y. Beauchamp, and P. Octeau, 5:63-72 (No. 9111).

Effect of Humic Acid on Leaching of CCA From Treated Wood, P.A. Cooper, D. Jeremic, J.L. Taylor, Y.T. Ung, and F. Kazi, 9:73-77 (No. 9163).

Effect of Moisture Content on Treatability of Japanese Red Pine, Japanese Larch, and Ezo Spruce With Chromated Copper Arsenate, G.-H. Kim and J.-J. Kim, 6:64-66 (No. 9137).

Effect of Polyvinyl Pyrrolidone on the Dimensional Stability and Leachability of Copper From Wood Treated With Ammoniacal Copper Formulations, P. Vasishth and D. Nicholas, 1:51-54 (No. 9077).

Effect of Preservative Treatment on Survival of Fungi in Western Red Cedar Utility Poles, J.J. Morrell, C.M. Freitag, and C. Eddington, 9:69-72 (No. 9155).

2001 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 2001 *Forest Products Journal*, volume 51, are listed both by subject and by author. Reprints of most articles are available at $6 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $6 minimum charge plus $5 handling charge per order. There is a charge of $6 for a copy of the 2001 *FPJ* Subject and Author Index.

ADHESIVES/ADHESION

Influence of Splice Length on Strengths of Glued Splice OSB Joints in Tension, Y.H. Chui and C. Ni, 2:23-28 (No. 9100).

Reducing Warp and Checking in Plantation-Grown Yellow-Poplar 4 by 4's by Reversing Part Positions and Gluing in the Green Condition, R. Serrano and D. Cassens, 11/12:37-40 (No. 9231).

AIR AND WATER QUALITY

Estimated U.S. Forest and Paper Industry CO_2 Emissions Resulting From Compliance With Federal Environmental Regulations, S.C. Stratton, R.A. Miner, D.H. Word, E.H. Mannisto, and H.I. Mannisto, 5:25-31 (No. 9110).

Response Surface Methodology Study of VOCs in Plywood Press Emissions, A. Barry, R. Lépine, R. Lovell, and S. Raymond, 1:65-73 (No. 9082).

ANATOMY AND QUALITY

Growth Characteristics of Moso Bamboo in South Carolina, A.W.C. Lee and S.C. Addis, 2:88-89 (No. 9090).

Modification of the Growth Habit of the Softwood Disfiguring Fungus *Ophiostoma piceae* by Monoterpene Vapors, C. Payne, S. Woodward, and J.A. Petty, 7/8:89-92 (No. 9237).

Wood Machining Properties of White Spruce From Plantation Forests, R.E. Hernández, C. Bustos, Y. Fortin, and J. Beaulieu, 6:82-88 (No. 9140).

CHEMISTRY AND CHEMICAL MODIFICATION

Physical, Mechanical, and Chemical Properties of Steamed Beech Wood, N. Yilgor, O. Unsal, and S.N. Kartal, 11/12:89-93 (No. 9183).

Seasonal Variation of Southern Pine Terpenes, T.E. Conners, L.L. Ingram, W. Su, H. Yan, S. Banerjee, A.T. Dalton, M.C. Templeton, and S.V. Diehl, 6:89-94 (No. 9029).

COMPOSITES AND ENGINEERED PRODUCTS

Bending Strength of Gusset-Plate Joints Constructed of Wood Composites, J. Zhang, D.E. Lyon, F. Quin, and B. Tackett, 5:40-44 (No. 9135).

Flake Orientation Effects on Physical and Mechanical Properties of Sweetgum Flakeboard, T.F. Shupe, C.Y. Hse, and E.W. Price, 9:38-43 (No. 9138).

The Influence of Furnish Moisture Content and Press Closure Rate on the Formation of the Vertical Density Profile in Oriented Strandboard, C.K. Andrews, P.M. Winistorfer, and R.M. Bennett, 5:32-39 (No. 8930).

Influence of Splice Length on Strengths of Glued Splice OSB Joints in Tension, Y.H. Chui and C. Ni, 2:23-28 (No. 9100).

Laboratory Decay Resistance of Woodfiber/Thermoplastic Composites, S. Verhey, P. Laks, and D. Richter, 9:44-49 (No. 9160).

Mechanical Properties of Composites Made With Wood Fiber and Recycled Tire Rubber, X.M. Song and J.-Y. Hwang, 5:45-51 (No. 8549).

Medium Density Fiberboard Made From *Eucalyptus saligna*, A.M. Krzysik, J.H. Muehl, J.A. Youngquist, and F.S. Franca, 10:47-50 (No. 9175).

A Model of the Effect of Strand Length and Strand Thickness on the Strength Properties of Oriented Wood Composites, D. Barnes, 2:36-46 (No. 9066).

Particleboard Made From Remediated CCA-Treated Wood: Evaluation of Panel Properties, C.A. Clausen, S.N. Kartal, and J. Muehl, 7/8:61-64 (No. 9159).

Performance of Fasteners in Wood Flour-Thermoplastic Composite Panels, R.H. Falk, D.J. Vos, S.M. Cramer, and B.W. English, 1:55-61 (No. 9080).

Permanent Bracing Design for MPC Wood Roof Truss Webs and Chords, C.R. Underwood, F.E. Woeste, J.D. Dolan, and S.M. Holzer, 7/8:73-81 (No. 9128).

Technical Feasibility of Structural Flakeboard Made From Mixed Hardwoods and Cypress From Northern Florida, T.F. Shupe, C.Y. Hse, and E.W. Price, 1:62-64 (No. 9085).

DETERIORATION/DEGRADATION AND PRESERVATION

Application of Radio-Frequency Heating to Utility Poles. Part 2. Accelerated Fixation of Chromated Copper Arsenate, F. Fang, J.N.R. Ruddick, and S. Avramidis, 9:53-58 (No. 9141).

Application of Radio-Frequency Heating to Utility Poles. Part 3. The Use of RF Heating to Eradicate Decay Fungi in Pole Material, F. Fang, J.N.R. Ruddick, and S. Avramidis, 11/12:51-55 (No. 9147).

Arrest of Fungal Pre-Infections in Raw Logs and Freshly Sawn Lumber of Radiata Pine Using Sentry®, B. Kreber, M. Kimberley, D. Eden, C. Chittenden, J. Van der Waals, R. Wakeling, and I. Dorsey, 10:66-72 (No. 9173).

Control of Graystain in Yellow-Poplar Lumber by Log Fumigation With Sulfuryl Fluoride, E.L. Schmidt, D.L. Cassens, and B.A. Jordan, 9:50-52 (No. 9149).

The Durability of Yellow-Poplar and American Beech Treated With Chromated Copper Arsenate, J.J. Slahor, C.C. Hassler, and B. Dawson-Andoh, 4:62-66 (No. 9154).

Durability of Yellow-Poplar and American Beech Treated With Creosote and Borate, J.J. Slahor, H.M. Barnes, B. Dawson-Andoh, T.L. Amburgey, and C.C. Hassler, 7/8:51-55 (No. 9248).

The Durability of Yellow-Poplar and Red Maple Treated With ACQ-B, J.J. Slahor, C.C. Hassler, and B. Dawson-Andoh, 9:59-62 (No. 9250).

Effect of Gaff Design on Linemen's Perception of the Climbability of Red Pine Utility Poles of Pre-Selected Wood Hardness, R. Gilbert, A. Besner, Y. Beauchamp, and P. Octeau, 5:63-72 (No. 9111).

Effect of Humic Acid on Leaching of CCA From Treated Wood, P.A. Cooper, D. Jeremic, J.L. Taylor, Y.T. Ung, and F. Kazi, 9:73-77 (No. 9163).

Effect of Moisture Content on Treatability of Japanese Red Pine, Japanese Larch, and Ezo Spruce With Chromated Copper Arsenate, G.-H. Kim and J.-J. Kim, 6:64-66 (No. 9137).

Effect of Polyvinyl Pyrrolidone on the Dimensional Stability and Leachability of Copper From Wood Treated With Ammoniacal Copper Formulations, P. Vasishth and D. Nicholas, 1:51-54 (No. 9077).

Effect of Preservative Treatment on Survival of Fungi in Western Red Cedar Utility Poles, J.J. Morrell, C.M. Freitag, and C. Eddington, 9:69-72 (No. 9155).

Effects of Deck Washes and Brighteners on the Leaching of CCA Components, A. Taylor, P.A. Cooper, and Y.T. Ung, 2:69-72 (No. 9099).

Fumigation of Red Beech Logs for Reducing Gray Stain in Lumber, E.L. Schmidt, B. Kreber, and S. Boon, 5:89-91 (No. 9132).

Heartwood Temperatures of Red Pine Pole Stock During Pentachlorophenol Pressure Treatment and Presence of Decay Fungi Prior to Treatment, E.L. Schmidt and C. Westberg, 11/12:41-44 (No. 9176).

Inadequate Redrying Linked to Dimensional Instability of CCA-Treated Southern Pine Lumber, T.F. Shupe, S.T. Lebow, E.T. Choong, and M. Xiong, 5:59-62 (No. 9130).

Laboratory Decay Resistance of Woodfiber/Thermoplastic Composites, S. Verhey, P. Laks, and D. Richter, 9:44-49 (No. 9160).

A Method for the Prevention of Wood Decay From Nail Penetration, D.-Q. Yang, 4:67-70 (No. 9115).

Modification of the Growth Habit of the Softwood Disfiguring Fungus *Ophiostoma piceae* by Monoterpene Vapors, C. Payne, S. Woodward, and J.A. Petty, 7/8:89-92 (No. 9237).

Nondestructive Evaluation of Potential Quality of Creosote-Treated Piles Removed From Service, X. Wang, R.J. Ross, J.R. Erickson, J.W. Forsman, G.D. McGinnis, and, R.C. De Groot, 2:63-68 (No. 9092).

Particleboard Made From Remediated CCA-Treated Wood: Evaluation of Panel Properties, C.A. Clausen, S.N. Kartal, and J. Muehl, 7/8: 61-64 (No. 9159).

Protecting Wood Decks From Biodegradation and Weathering: Evaluation of Deck Finish Systems, J.J. Morrell, P.F. Schneider, and R.S. Williams, 11/12:27-32 (No. 9145).

Residual CCA Levels in CCA-Treated Poles Removed From Service, P.A. Cooper, D. Jeremic, and J.L. Taylor, 10:58-62 (No. 9162).

Staining Ability of Various Sapstaining Fungi on Jack Pine Short Log Sections, D.-Q. Yang, 2:73-76 (No. 9094).

Thermal Degradation of Fire-Retardant-Treated Wood: Predicting Residual Service Life, J.E. Winandy, 2:47-54 (No. 9095).

Timber Production From Reclaimed Creosote-Treated Wood Pilings: Economic Analysis and Quality Evaluation, S.Q. Shi, D.J. Gardner, D. Pendleton, and T. Hoffard, 11/12:45-50 (No. 9193).

Treatment and Redrying of Western Hemlock Plywood, A. Khouadja and A.M. Barnes, 1:74-80 (No. 9091).

Drying and Storage

Accelerated Kiln Schedules for Drying of Hackberry, Red Oak, and Sweetgum Lumber, R. Shmulsky and H. Castillo, 11/12: 33-36 (No. 9273).

Application of Radio-Frequency Heating to Utility Poles. Part 1. Radio-Frequency/Vacuum Drying of Roundwood, F. Fang, J.N.R. Ruddick, and S. Avramidis, 7/8: 56-60 (No. 9139).

Assessment of Comercial In-Line Meters for Measuring the Moisture Content of Radiata Pine Lumber, I. Simpson and T. Haslett, 3:65-68 (No. 9112).

Check Development on Jack Pine Logs in Eastern Canada, D.-Q. Yang and R. Beauregard, 10:63-65 (No. 9281).

Effect of Pressure Steaming on Twist and Stability of Radiata Pine Lumber, A.N. Haslett and M. Dakin, 2:85-87 (No. 9104).

Effects of High-Temperature Drying on Bending Strength of Red Pine Poles, Y.H. Chui, A. Taylor, and P. Cooper, 7/8:47-50 (No. 9129).

Evalution of Energy Conservation by Second-Stage Drying, R. Shmulsky and F.W. Taylor, 3:75-78 (No. 9125).

Inadequate Redrying Linked to Dimensional Instability of CCA-Treated Southern Pine Lumber, T.F. Shupe, S.T. Lebow, E.T. Choong, and M. Xiong, 5:59-62 (No. 9130).

Method for Esimating Air-Drying Times of Lumber, W.T. Simpson and C.A. Hart, 11/12:56-63 (No. 9197).

Modelling of Airflow in Wood Kilns, L. Hua, E. Bibeau, P. He, I. Gartshore, M. Salcudean, Z. Bian, and S. Chow, 6:74-81 (No. 9134).

Moisture Meter Correction Factors for Four Brazilian Wood Species, C.M. Gillis, W.C. Stephens, and P.N. Peralta, 4:83-86 (No. 9181).

Physical, Mechanical, and Drying Properties Associated With Bacterial Wetwood in Red Oaks, Z. Xu, T.D. Leininger, A.W.C. Lee, and F.H. Tainter, 3:79-84 (No. 9086).

Relationship Between Longitudinal Stress Wave Transit Time and Moisture Content of Lumber During Kiln-Drying, W.T. Simpson and X. Wang, 10:51-54 (No. 9282).

Spiral Grain on Logs Under Bark Reveals Twist-Prone Raw Material, R. Kliger, 6:67-73 (No. 9136).

Vacuum Drying of Small Wood Components at Room Temperature, Z. Chen and F.M. Lamb, 10:55-57 (No. 9279).

Engineering and Mechanical Properties

Bending Fatigue Life of Two-Pin Dowel Joints Constructed of Wood and Wood Composites, J. Zhang, F. Quin, and B. Tackett, 10:73-78 (No. 9184).

Bending Strength and Stiffness of Two-Pin Dowel Joints Constructed of Wood and Wood Composites, J. Zhang, F. Quin, and B. Tackett, 2:29-35 (No. 9101).

Bending Strength of Gusset-Plate Joints Constructed of Wood Composites, J. Zhang, D.E. Lyon, F. Quin, and B. Tackett, 5:40-44 (No. 9135).

A Circular Internal Bond Test for Predicting the Holding Strength of Furniture Fasteners, H. Akcay and C.A. Eckelman, 5:73-78 (No. 9127).

Construction With Small-Diameter Roundwood, E.G. Stern, 4:71-82 (No. 9097).

Design and Testing of Wood School Desk Frames Suitable for Production by Low Technology Methods From Waste Wood Residues, E. Haviarova, C. Eckelman, and Y. Erdil, 5:79-88 (No. 9123).

Determination of the Relationships Between Brinell and Janka Hardness of Eastern Beech (*Fagus orientalis* Lipsky), I. Bektas, M.H. Alma, and N. As, 11/12:84-88 (No. 9166).

Dynamic Performance of Perforated Light-Frame Shear Walls With Various End Restraints, C.P. Heine and J.D. Dolan, 7/8: 65-72 (No. 9083).

Edgewise Flexural Properties and Modulus of Rigidity of Different Sizes of Southern Pine LVL and Plywood, E.J. Biblis, 1:81-84 (No. 9093).

Effect of Heart Checks on Flexural Properties of Reclaimed 6 by 8 Douglas-Fir Timbers, D.W. Green, R.H. Falk, and S.F. Lantz, 7/8:82-88 (No. 9028).

Effects of High-Temperature Drying on Bending Strength of Red Pine Poles, Y.H. Chui, A. Taylor, and P. Cooper, 7/8:47-50 (No. 9129).

Engineering Properties of Hem-Fir Used in Japanese Post and Beam Housing, F. Lam, J.D. Barrett, and S. Nakajima, 10:79-87 (No. 9113).

Flake Orientation Effects on Physical and Mechanical Properties of Sweetgum Flakeboard, T.F. Shupe, C.Y. Hse, and E.W. Price, 9:38-43 (No. 9138).

Influence of Specific Gravity on Embedment Gaps in Metal-Plate-Connected Truss Joints, B.K. Via, A. Zink-Sharp, F. Woeste, and J.D. Dolan, 10:88-92 (No. 9218).

Permanent Bracing Design for MPC Wood Roof Truss Webs and Chords, C.R. Underwood, F.E. Woeste, J.D. Dolan, and S.M. Holzer, 7/8:73-81 (No. 9128).

Physical, Mechanical, and Chemical Properties of Steamed Beech Wood, N. Yilgor, O.

Unsal, and S.N. Kartal, 11/12: 89-93 (No. 9183).

Predicting Modulus of Rupture of Solid and Finger-Jointed Tropical African Hard- woods Using Longitudinal Vibration, J. Ayarkwa, Y. Hirashima, and Y. Sasaki, 1:85-92 (No. 9078).

Rapid Prediction of Wood Stiffness From Microfibril Angle and Density, R. Evans and J. Ilic, 3:53-57 (No. 9105).

Size Effect on Shear Strength Measured by the ASTM Method, E.M. Lang and Z. Kovacs, 3:49-52 (No. 8976).

Tension Parallel to Grain, Pure Flexural Stiffness, and Modulus of Rigidity of Clear Wood of Seven Eastern Red Oaks, E.J. Biblis, 4:87-89 (No. 9124).

Finishing and Overlaying

Protecting Wood Decks From Biodegradation and Weathering: Evaluation of Deck Finish Systems, J.J. Morrell, P.F. Schneider, and R.S. Williams, 11/12: 27-32 (No. 9145).

Furniture and Hardwood Veneer/Plywood

A Brief Look at Raw Material Usage in the Furniture and Cabinet Industries in the Southern United States, R.P. Vlosky and Q. Wu, 9:25-29 (No. 9251).

A Circular Internal Bond Test for Predicting the Holding Strength of Furniture Fasteners, H. Akcay and C.A. Eckelman, 5:73-78 (No. 9127).

Considerations in the Design and Development of School Furniture for Developing Regions Based on Local Resources, C. Eckelman, E. Haviarova, H. Zui, and H. Gibson, 6:56-63 (No. 9122).

Design and Testing of Environmentally Friendly Wood School Chairs for Developing Countries, E. Haviarova, C. Eckelman, and Y. Erdil, 3:58-64 (No. 9116).

Design and Testing of Wood School Desk Frames Suitable for Production by Low Technology Methods From Waste Wood Residues, E. Haviarova, C. Eckelman, and Y. Erdil, 5:79-88 (No. 9123).

An Investigation of Hardwood Plywood Markets. Part 2. Fixture Manufacturers, C.L. Forbes, L.G. Jahn, and P.A. Araman, 6:25-31 (No. 9121).

Lumber Production

Characterizing Adopters of Automated Lumber Grading Systems, D.W. Cumbo, R.L. Smith, and D.E. Kline, 7/8:37-43 (No. 9120).

The Durability of Yellow-Poplar and Red Maple Treated With ACQ-B, J.J. Slahor, C.C. Hassler, and B. Dawson-Andoh, 9:59-62 (No. 9250).

Efficacy of Curtailment Announcements as a Predictor of Lumber Supply, H. Spelter, 7/8:44-46 (No. 9238).

The Influence of Missing Bark on Measurements Performed With a 3D Log Scanner, S. Chiorescu and S. Grundberg, 9:78-86 (No. 9182).

Lumber Strength Grading Using X-Ray Scanning, G.S. Schajer, 1:43-50 (No. 9075).

The Optimum Benefit Bundle and Promotion Strategy for Automated Lumber Grading Systems, D.W. Cumbo, D.E. Kline, and R.L. Smith, 9:63-68 (No. 9096).

Marketing, Management, and Economics

A Brief Look at Raw Material Usage in the Furniture and Cabinet Industries in the Southern United States, R.P. Vlosky and Q. Wu, 9:25-29 (No. 9251).

Certified Wood Products Merchants in the United States: A Comparison Between 1995 and 1998, S. Humphries, R.P. Vlosky, and D. Carter, 6:32-38 (No. 9131).

A Characterization of the U.S. Residential Deck Material Market, S.R. Shook and I.L. Eastin, 4:28-36 (No. 9118).

Characterizing Adopters of Automated Lumber Grading Systems, D.W. Cumbo, R.L. Smith, and D.E. Kline, 7/8:37-43 (No. 9120).

A Comparison of Two Input-Output Approaches for Investigating Regional Economic Impacts of the Forest Products Industry in the Pacific Northwest and the South, B.M. Cox and I.A. Munn, 6:39-46 (No. 9143).

Considerations in the Design and Development of School Furniture for Developing Regions Based on Local Resources, C. Eckelman, E. Haviarova, H. Zui, and H. Gibson, 6:56-63 (No. 9122).

Decision Making in the Purchase of Siding: A Survey of Architects, Contractors, and Homeowners in the U.S. Northeast, D.T. Damery and P. Fisette, 7/8:29-36 (No. 9153).

Efficacy of Curtailment Announcements as a Predictor of Lumber Supply, H. Spelter, 7/8:44-46 (No. 9238).

Employment Structure and Training Needs in the Louisiana Value-Added Wood Products Industry, R.P. Vlosky and N.P. Chance, 3:34-41 (No. 9119).

Enhancing the Profitability of a Vertically Integrated Wood Products Production System. Part 1. A Multistage Modelling Approach, H.F. Carino and D.B. Willis III, 4:37-44 (No. 8997).

Enhancing the Profitability of a Vertically Integrated Wood Products Production System. Part 2. A Case Study, H.F. Carino and D.B. Willis III, 4:45-53 (No. 9144).

Industry-Wide Product Promotion Within Commodity Industries: An Opportunity for the Forest Products Industry?, R.C. Anderson and J.L. Bowyer, 11/12:64-69 (No. 9171).

An Investigation of Hardwood Plywood Markets. Part 1. Architectural Woodworkers, C.L. Forbes, L.G. Jahn, and P.A. Araman, 3:17-24 (No. 9106).

An Investigation of Hardwood Plywood Markets. Part 2. Fixture Manufacturers, C.L. Forbes, L.G. Jahn, and P.A. Araman, 6:25-31 (No. 9121).

Japanese Attendee Objectives for Building Products Trade Shows: A Cross-National Comparison, P.M. Smith, K. Hama, and T.M. Smith, 11/12:78-83 (No. 9199).

Material Substitution in the U.S. Residential Construction Industry, 1994 versus 1998, I.L. Eastin, S.R. Shook, and S.J. Fleishman, 9:30-37 (No. 9161).

A National Profile of the U.S. Hardwood Sawmill Industry, S.A. Bowe, R.L. Smith, and P.A. Araman, 10:25-31 (No. 9189).

Perceived Obligations of Future Forest Industry Employees: A Psychological Contracts Perspective, J.H. Michael, 10:39-46 (No. 9170).

Quality Assurance for Value-Added Wood Producers in British Columbia, R.A. Kozak and T.C. Maness, 6:47-55 (No. 9148).

Timber Production From Reclaimed Creosote-Treated Wood Pilings: Economic Analysis and Quality Evaluation, S.Q. Shi, D.J. Gardner, D. Pendleton, and T. Hoffard, 11/12:45-50 (No. 9193).

U.S. - Canada Softwood Lumber Trade Disputes and Lumber Price Volatility, D. Zhang and C. Sun, 4:21-27 (No. 9207).

Use and Production of Solid Sawn Timbers in the United States, G. Jackson, A.L. Hammett, and J. Howard, 7/8:23-28 (No. 9142).

Wood Products Cooperatives: Overview and Exploratory Analysis, S.R. Shook, Y. Zhang, and F.G. Wagner, 3:25-33 (No. 9114).

Milling and Machining

Volume and Value Variation With Opening Face Position: An Investigation With Pruned Softwood Logs, C.L. Todoroki, 1:36-42 (No. 9087).

Wood Machining Properties of White Spruce From Plantation Forests, R.E. Hernández, C. Bustos, Y. Fortin, and J. Beaulieu, 6:82-88 (No. 9140).

Physics and Moisture Relations

Assessment of Comercial In-Line Meters for Measuring the Moisture Content of Radiata Pine Lumber, I. Simpson and T. Haslett, 3:65-68 (No. 9112).

Effect of Moisture Content on Treatability of Japanese Red Pine, Japanese Larch, and Ezo Spruce With Chromated Copper Arsenate, G.-H. Kim and J.-J. Kim, 6:64-66 (No. 9137).

Long-Term Monitoring of Timber Moisture Content Below the Fiber Saturation Point Using Wood Resistance Sensors, G. Dai and K. Ahmet, 5:52-58 (No. 9133).

Method for Esimating Air-Drying Times of Lumber, W.T. Simpson and C.A. Hart, 11/12:56-63 (No. 9197).

Moisture Meter Correction Factors for Four Brazilian Wood Species, C.M. Gillis, W.C. Stephens, and P.N. Peralta, 4:83-86 (No. 9181).

Physical, Mechanical, and Chemical Properties of Steamed Beech Wood, N. Yilgor, O. Unsal, and S.N. Kartal, 11/12:89-93 (No. 9183).

Proportional Surface Drying of Small Loblolly Pine Cubes at 120°C, R. Shmulsky, 4:90-92 (No. 9126).

Reducing Warp and Checking in Plantation-Grown Yellow-Poplar 4 by 4's by Reversing Part Positions and Gluing in the Green Condition, R. Serrano and D. Cassens, 11/12:37-40 (No. 9231).

Spiral Grain on Logs Under Bark Reveals Twist-Prone Raw Material, R. Kliger, 6:67-73 (No. 9136).

Process Control/ Quality Control

The Effects of Autocorrelation on Real-Time Statistical Process Control With Solutions for Forest Products Manufacturers, T.M. Young and P.M. Winistorfer, 11/12: 70-77 (No. 9191).

The Influence of Missing Bark on Measurements Performed With a 3D Log Scanner, S. Chiorescu and S. Grundberg, 9:78-86 (No. 9182).

Lumber Strength Grading Using X-Ray Scanning, G.S. Schajer, 1:43-50 (No. 9075).

The Optimum Benefit Bundle and Promotion Strategy for Automated Lumber Grading Systems, D.W. Cumbo, D.E. Kline, and R.L. Smith, 9:63-68 (No. 9096).

Quality Assurance for Value-Added Wood Producers in British Columbia, R.A. Kozak and T.C. Maness, 6:47-55 (No. 9148).

Reduction of Residual Stress in Logs by Direct Heat Treatment: Temperature Distribution Within the Furnace, M. Nogi, M. Yoshida, H. Yamamoto, and T. Okuyama, 3:69-74, (No. 9039).

Recycling and Residue Utilization

Effect of Heart Checks on Flexural Properties of Reclaimed 6 by 8 Douglas-Fir Timbers, D.W. Green, R.H. Falk, and S.F. Lantz, 7/8:82-88 (No. 9028).

Mechanical Properties of Composites Made With Wood Fiber and Recycled Tire Rubber, X.M. Song and J.-Y. Hwang, 5:45-51 (No. 8549).

Performance of Pallet Parts Recovered From Used Wood Pallets, J.W. Clarke, M.S. White, and P.A. Araman, 2:55-62 (No. 9074).

Testing and Test Methodology

Rapid Prediction of Wood Stiffness From Microfibril Angle and Density, R. Evans and J. Ilic, 3:53-57 (No. 9105).

Timber Production and Harvesting

Assessing the Role of the Harvester Within the Forestry-Wood Chain, S. Chiorescu and A. Grönlund, 2:77-84 (No. 9109).

Designation of Timber Extraction Routes in a GIS Using Road Maintenance Cost Data, A.M. Martin, P.M.O. Owende, N.M. Holden, S.M. Ward, and M.J. O'Mahony, 10:32-38 (No. 9157).

Georgia's Logging Businesses, 1987 to 1997, W.D. Greene, B.D. Jackson, and J.D. Culpepper, 1:25-28 (No. 9035).

Harvesting Cost Model for Small Trees in Natural Stands in the Interior Northwest, B.R. Hartsough, X. Zhang, and R.D. Fight, 4:54-61 (No. 9102).

Potential Impacts of Increased Management Intensities on Planted Pine Growth and Yield and Timber Supply Modeling in the South, J.P. Siry, F.W. Cubbage, and A.J. Malmquist, 3:42-48 (No. 9076).

Role of Intermediaries in Technology Transfer in the Logging Industry: A Case Study With Portable Timber Bridges, R.-J. Shiau, R.L. Smith, and E.T. Cesa, 5:17-24 (No. 9034).

Wood and The Environment

Certified Wood Products Merchants in the United States: A Comparison Between 1995 and 1998, S. Humphries, R.P. Vlosky, and D. Carter, 6:32-38 (No. 9131).

Diversity, Productivity, Profitability, Sustainability, and the Tao of Underutilized Species, R.L. Youngs and A.L. Hammett, 1:29-35 (No. 9068).

Feature Articles

After the Hurricane: Forest Sector Reconstruction in Honduras, A. Chavez, M.A. Dunn, P.A. Monroe, T.F. Shupe, L. Velupillai, D.A. Vlosky, and R.P. Vlosky, 11/12:18-24 (No. 9247).

Agricultural Residues: An Exciting Bio-Based Raw Material for the Industry, J.L. Bowyer and V.E. Stockmann, 1:10-21 (No. 9090).

Competitiveness of U.S. Wood Furniture Manufacturers, A. Schuler, R. Taylor, and P. Araman, 7/8:14-20 (No. 9244).

CORRIM: A Report of Progress and a Glimpse of the Future, J. Bowyer, D. Briggs, L. Johnson, B. Kasal, B. Lippke, J. Meil, M. Milota, W. Trusty, C. West, J. Wilson, and P. Winistorfer, 10:10-22 (No. 9246).

Exploring the Uses for Small-Diameter Trees, S.L. LeVan-Green and J. Livingston, 9:10-21 (No. 9245).

Forest Products Research and IUFRO: History and Potential, R.L. Youngs and J.A. Youngquist, 2:12-19 (No. 9240).

Out of the Woodwork: Wood Industry Rallies Together to Be Constructive, J. Gleason, 5:8-14 (No. 7242).

Partnership for Advancing Technology in Housing, E. Burdock, M. Ritter, J. Livingston, and S. Carnes, 3:8-14 (No. 9241).

Wood Adhesive Innovations and Applications in North America, T. Sellers, Jr., 6:12-22 (No. 9243).

A

Addis, S.C., see Lee, A.W.C.

Ahmet, K., see Dai, G.

Akcay, H. and C.A. Eckelman, A Circular Internal Bond Test for Predicting the Holding Strength of Furniture Fasteners, 5:73-78 (No. 9127).

Alma, M.H., see Bektas, I.

Amburgey, T.L., see Slahor, J.J.

Anderson, R.C. and J.L. Bowyer, Industry-Wide Product Promotion Within Commodity Industries: An Opportunity for the Forest Products Industry?, 11/12:64-69 (No. 9171).

Andrews, C.K., P.M. Winistorfer, and R.M. Bennett, The Influence of Furnish Moisture Content and Press Closure Rate on the Formation of the Vertical Density Profile in Oriented Strandboard, 5:32-39 (No. 8930).

Araman, P., see Schuler, A.

Araman, P.A., see Bowe, S.A.

Araman, P.A., see Clarke, J.W.

Araman, P.A., see Forbes, C.L.

As, N., see Bektas, I.

Avramidis, S., see Fang, F.

Ayarkwa, J., Y. Hirashima, and Y. Sasaki, Predicting Modulus of Rupture of Solid and Finger-Jointed Tropical African Hardwoods Using Longitudinal Vibration, 1:85-92 (No. 9078).

B

Banerjee, S., see Conners, T.E.

Barnes, D., A Model of the Effect of Strand Length and Strand Thickness on the Strength Properties of Oriented Wood Composites, 2:36-46 (No. 9066).

Barnes, H.M., see Khouadja, A.

Barnes, H.M., see Slahor, J.J.

Barrett, J.D., see Lam, F.

Barry, A., R. Lepine, R. Lovell, and S. Raymond, Response Surface Methodology Study of VOCs in Plywood Press Emissions, 1:65-73 (No. 9082).

Beauchamp, Y., see Gilbert, R.

Beaulieu, J., see Hernández, R.E.

Beauregard, R., s. Yang, D.-Q.

Bektas, I., M.H. Alma, and N. As, Determination of the Relationships Between Brinell and Janka Hardness of Eastern Beech (*Fagus orientalis* Lipsky), 11/12:84-88 (No. 9166).

Bennett, R.M., see Andrews, C.K.

Besner, A., see Gilbert, R.

Bian, Z., see Hua, L.

Bibeau, E., see Hua, L.

Biblis, E.J., Edgewise Flexural Properties and Modulus of Rigidity of Different Sizes of Southern Pine LVL and Plywood, 1:81-84 (No. 9093).

Biblis, E.J., Tension Parallel to Grain, Pure Flexural Stiffness, and Modulus of Rigidity of Clear Wood of Seven Eastern Red Oaks, 4:87-89 (No. 9124).

Boon, S., see Schmidt, E.L.

Bowe, S.A., R.L. Smith, and P.A. Araman, A National Profile of the U.S. Hardwood Sawmill Industry, 10:25-31 (No. 9189).

Bowyer, J., D. Briggs, L. Johnson, B. Kasal, B. Lippke, J. Meil, M. Milota, W. Trusty, C. West, J. Wilson, and P. Winistorfer, CORRIM: A Report of Progress and a Glimpse of the Future, 10:10-22 (No. 9246).

Bowyer, J.L. and V.E. Stockmann, Agricultural Residues: An Exciting Bio-Based Raw Material for the Industry, 1:10-21 (No. 9090).

Bowyer, J.L., see Anderson, R.C.

Briggs, D., see Bowyer, J.

Burdock, E., M. Ritter, J. Livingston, and S. Carnes, Partnership for Advancing Technology in Housing, 3:8-14 (No. 9241).

Bustos, C., see Hernández, R.E.

C

Carino, H.F. and D.B. Willis III, Enhancing the Profitability of a Vertically Integrated Wood Products Production System. Part 1. A Multistage Modelling Approach, 4:37-44 (No. 8997).

Carino, H.F. and D.B. Willis III, Enhancing the Profitability of a Vertically Integrated Wood Products Production System. Part 2. A Case Study, 4:45-53 (No. 9144).

Carnes, S., see Burdock, E.

Carter, D., see Humphries, S.

Cassens, D., see Serrano, R.

Cassens, D.L., see Schmidt, E.L.

Castillo, H., see Shmulsky, R.

Cesa, E.T., see Shiau, R.-J.

Chance, N.P., see Vlosky, R.P.

Chavez, A., M.A. Dunn, P.A. Monroe, T.F. Shupe, L. Velupillai, D.A. Vlosky, and R.P. Vlosky, After the Hurricane: Forest Sector Reconstruction in Honduras, 11/12:18-24 (No. 9247).

Chen, Z. and F.M. Lamb, Vacuum Drying of Small Wood Components at Room Temperature, 10:55-57 (No. 9279).

Chiorescu, S. and A. Grönlund, Assessing the Role of the Harvester Within the Forestry-Wood Chain, 2:77-84 (No. 9109).

Chiorescu, S. and S. Grundberg, The Influence of Missing Bark on Measurements Performed With a 3D Log Scanner, 9:78-86 (No. 9182).

Chittenden, C., see Kreber, B.

Choong, E.T., see Shupe, T.F.

Chow, S., see Hua, L.

Chui, Y.H. and C. Ni, Influence of Splice Length on Strengths of Glued Splice OSB Joints in Tension, 2:23-28 (No. 9100).

Chui, Y.H., A. Taylor, and P. Cooper, Effects of High-Temperature Drying on Bending Strength of Red Pine Poles, 7/8:47-50 (No. 9129).

Clarke, J.W., M.S. White, and P.A. Araman, Performance of Pallet Parts Recovered From Used Wood Pallets, 2:55-62 (No. 9074).

Clausen, C.A., S.N. Kartal, and J. Muehl, Particleboard Made From Remediated CCA-Treated Wood: Evaluation of Panel Properties, 7/8:61-64 (No. 9159).

Conners, T.E., L.L. Ingram, W. Su, H. Yan, S. Banerjee, A.T. Dalton, M.C. Templeton, and S.V. Diehl, Seasonal Variation of Southern Pine Terpenes, 6:89-94 (No. 9029).

Cooper, P., see Chui, Y.H.

Cooper, P.A., D. Jeremic, and J.L. Taylor, Residual CCA Levels in CCA-Treated Poles Removed From Service, 10:58-62 (No. 9162).

Cooper, P.A., D. Jeremic, J.L. Taylor, Y.T. Ung, and F. Kazi, Effect of Humic Acid on Leaching of CCA From Treated Wood, 9:73-77 (No. 9163).

Cooper, P.A., see Taylor, A.

Cox, B.M. and I.A. Munn, A Comparison of Two Input-Output Approaches for Investigating Regional Economic Impacts of the Forest Products Industry in the Pacific Northwest and the South, 6:39-46 (No. 9143).

Cramer, S.M., see Falk, R.H.

Cubbage, F.W., see Siry, J.P.

Culpepper, J.D., see Greene, W.D.

Cumbo, D.W., D.E. Kline, and R.L. Smith, The Optimum Benefit Bundle and Promotion Strategy for Automated Lumber Grading Systems, 9:63-68 (No. 9096).

Cumbo, D.W., R.L. Smith, and D.E. Kline, Characterizing Adopters of Automated Lumber Grading Systems, 7/8:37-43 (No. 9120).

D

Dai, G. and K. Ahmet, Long-Term Monitoring of Timber Moisture Content Below the Fiber Saturation Point Using Wood Resistance Sensors, 5:52-58 (No. 9133).

Dakin, M., see Haslett, A.N.

Dalton, A.T., see Conners, T.E.

Damery, D.T. and P. Fisette, Decision Making in the Purchase of Siding: A Survey of Architects, Contractors, and Homeowners in the U.S. Northeast, 7/8:29-36 (No. 9153).

Dawson-Andoh, B., see Slahor, J.J.

De Groot, R.C., see Wang, X.

Diehl, S.V., see Conners, T.E.

Dolan, J.D., see Heine, C.P.

Dolan, J.D., see Underwood, C.R.

Dolan, J.D., see Via, B.K.

Dorset, I., see Kreber, B.

Dunn, M.A., see Chavez, A.

E

Eastin, I.L., S.R. Shook, and S.J. Fleishman, Material Substitution in the U.S. Residential Construction Industry, 1994 versus 1998, 9:30-37 (No. 9161).

Eastin, I.L., see Shook, S.R.

Eckelman, C., E. Haviarova, H. Zui, and H. Gibson, Considerations in the Design and Development of School Furniture for Developing Regions Based on Local Resources, 6:56-63 (No. 9122).

Eckelman, C., see Haviarova, E.

Eckelman, C.A., see Akcay, H.

Eddington, C., see Morrell, J.J.

Eden, D., see Kreber, B.

English, B.W., see Falk, R.H.

Erdil, Y., see Haviarova, E.

Erickson, J.R., see Wang, X.

Evans, R. and JJ. Ilic, Rapid Prediction of Wood Stiffness From Microfibril Angle and Density, 3:53-57 (No. 9105).

F

Falk, R.H., J. Vos, S.M. Cramer, and B.W. English, Performance of Fasteners in Wood Flour-Thermoplastic Composite Panels, 1:55-61 (No. 9080).

Falk, R.H., see Green, D.W.

Fang, F., J.N.R. Ruddick, and S. Avramidis, Application of Radio-Frequency Heating to Utility Poles. Part 1. Radio-Frequency/Vacuum Drying of Roundwood, 7/8:56-60 (No. 9139).

Fang, F., J.N.R. Ruddick, and S. Avramidis, Application of Radio-Frequency Heating to Utility Poles. Part 2. Accelerated Fixation of Chromated Copper Arsenate, 9:53-58 (No. 9141).

Fang, F., J.N.R. Ruddick, and S. Avramidis, Application of Radio-Frequency Heating to Utility Poles. Part 3. The Use of RF Heating to Eradicate Decay Fungi in Pole Material, 11/12:51-55 (No. 9147).

Fight, R.D., see Hartsough, B.R.

Fisette, P., see Damery, D.T.

Fleishman, S.J., see Eastin, I.L.

Forbes, C.L., L.G. Jahn, and P.A. Araman, An Investigation of Hardwood Plywood Markets. Part 1. Architectural Woodworkers, 3:17-24 (No. 9106).

Forbes, C.L., L.G. Jahn, and P.A. Araman, An Investigation of Hardwood Plywood Markets. Part 2. Fixture Manufacturers, 6:25-31 (No. 9121).

Forsman, J.W., see Wang, X.

Fortin, Y., see Hernández, R.E.

Franca, F.S., see Krzysik, A.M.

Freitag, C.M., see Morrell, J.J.

G

Gardner, D.J., see Shi, S.Q.

Gartshore, I., see Hua, L.

Gibson, H., see Eckelman, C.

Gilbert, R., A. Besner, Y. Beauchamp, and P. Octeau, Effect of Gaff Design on Linemen's Perception of the Climbability of Red Pine Utility Poles of Pre-Selected Wood Hardness, 5:63-72 (No. 9111).

Gillis, C.M., W.C. Stephens, and P.N. Peralta, Moisture Meter Correction Factors for Four Brazilian Wood Species, 4:83-86 (No. 9181).

Gleason, J., Out of the Woodwork: Wood Industry Rallies Together to be Constructive, 5:8-14 (No. 9242).

Green, D.W., R.H. Falk, and S.F. Lantz, Effect of Heart Checks on Flexural Properties of Reclaimed 6 by 8 Douglas-Fir Timbers, 7/8:82-88 (No. 9028).

Greene, W. Dale, Ben D. Jackson, and Jack D. Culpepper, Georgia's Logging Businesses, 1987 to 1997, 1:25-28 (No. 9035).

Grönlund, A., see Chiorescu, S.

Grundberg, S., see Chiorescu, S.

H

Hama, K., see Smith, P.M.

Hammett, A.L., see Jackson, G.

Hammett, A.L., see Youngs, R.L.

Hart, C.A., see Simpson, W.T.

Hartsough, B.R., X. Zhang, and R.D. Fight, Harvesting Cost Model for Small Trees in Natural Stands in the Interior Northwest, 4:54-61 (No. 9102).

Haslett, A.N. and M. Dakin, Effect of Pressure Steaming on Twist and Stability of Radiata Pine Lumber, 2:85-87 (No. 9104).

Haslett, T., see Simpson, I.

Hassler, C.C., see Slahor, J.J.

Haviarova, E., C. Eckelman, and Y. Erdil, Design and Testing of Environmentally Friendly Wood School Chairs for Developing Countries, 3:58-64 (No. 9116).

Haviarova, E., C. Eckelman, and Y. Erdil, Design and Testing of Wood School Desk Frames Suitable for Production by Low Technology Methods From Waste Wood Residues, 5:79-88 (No. 9123).

Haviarova, E., see Eckelman, C.

He, P., see Hua, L.

Heine, C.P. and J.D. Dolan, Dynamic Performance of Perforated Light-Frame Shear Walls With Various End Restraints, 7/8:65-72 (No. 9083).

Hernández, R.E., C. Bustos, Y. Fortin, and J. Beaulieu, Wood Machining Properties of White Spruce From Plantation Forests, 6:82-88 (No. 9140).

Hirashima, Y., see Ayarkwa, J.

Hoffard, T.S, see Shi, S.Q.

Holden, N.M., see Martin, A.M.

Holzer, S.M., see Underwood, C.R.

Howard, J., see Jackson, G.

Hse, C.Y., see Shupe, T.F.

Hua, L., E. Bibeau, P. He, I. Gartshore, M. Salcudean, Z. Bian, and S. Chow, Modelling of Airflow in Wood Kilns, 6:74-81 (No. 9134).

Humphries, S., R.P. Vlosky, and D. Carter, Certified Wood Products Merchants in the United States: A Comparison Between 1995 and 1998, 6:32-38 (No. 9131).

Hwang, J.-Y., see Song, X.M.

I

Ilic, J., see Evans, R.

Ingram, L.L., see Conners, T.E.

J

Jackson, B.D., see Greene, W.D.

Jackson, G., A.L. Hammett, and J. Howard, Use and Production of Solid Sawn Timbers in the United States, 7/8:23-28 (No. 9142).

Jahn, L.G., see Forbes, C.L.

Jeremic, D., see Cooper, P.A.

Johnson, L., see Bowyer, J.

Jordan, B.A., see Schmidt, E.L.

K

Kartal, S.N., see Clausen, C.A.

Kartal, S.N., see Yilgor, N.

Kasal, B., see Bowyer, J.

Kazi, F., see Cooper, P.A.

Khouadja, A. and A.M. Barnes, Treatment and Redrying of Western Hemlock Plywood, 1:74-80 (No. 9091).

Kim, G.-H. and J.-J. Kim, Effect of Moisture Content on Treatability of Japanese Red Pine, Japanese Larch, and Ezo Spruce With Chromated Copper Arsenate, 6:64-66 (No. 9137).

Kim, J.-J., see Kim, G.-H.

Kimberley, M., see Kreber, B.

Kliger, R., Spiral Grain on Logs Under Bark Reveals Twist-Prone Raw Material, 6:67-73 (No. 9136).

Kline, D.E., see Cumbo, D.W.

Kovacs, Z., see Lang, E.M.

Kozak, R.A. and T.C. Maness, Quality Assurance for Value-Added Wood Producers in British Columbia, 6:47-55 (No. 9148).

Kreber, B., M. Kimberley, D. Eden, C. Chittenden, J. Van der Waals, R. Wakeling, and I. Dorsey, Arrest of Fungal Pre-Infections in Raw Logs and Freshly Sawn Lumber of Radiata Pine Using Sentry®, 10:66-72 (No. 9173).

Kreber, B., see Schmidt, E.L.

Krzysik, A.M., J.H. Muehl, J.A. Youngquist, and F.S. Franca, Medium Density Fiberboard Made From *Eucalyptus saligna*, 10:47-50 (No. 9175).

L

Laks, P., see Verhey, S.

Lam, F., J.D. Barrett, and S. Nakajima, Engineering Properties of Hem-Fir Used in Japanese Post and Beam Housing, 10:79-87 (No. 9113).

Lamb, F.M., see Chen, Z.

Lang, E.M. and Z. Kovacs, Size Effect on Shear Strength Measured by the ASTM Method, 3:49-52 (No. 8976).

Lantz, S.F., see Green, D.W.

Lebow, S.T., see Shupe, T.F.

Lee, A.W.C. and S.C. Addis, Growth Characteristics of Moso Bamboo in South Carolina, 2:88-89 (No. 9090).

Lee, A.W.C., see Xu, Z.

Leininger, T.D., see Xu, Z.

Lépine, R., see Barry, A.

LeVan-Green, S.L. and J. Livingston, Exploring the Uses for Small-Diameter Trees, 9:10-21 (No. 9245).

Lippke, B., see Bowyer, J.

Livingston, J., see Burdock, E.

Livingston, J., see LeVan-Green, S.L.

Lovell, R. see Barry, A.

Lyon, D.E., see Zhang, J.

M

Malmquist, A.J., see Siry, J.P.

Maness, T.C., see Kozak, R.A.

Mannisto, E.H., see Stratton, S.C.

Mannisto, H.I., see Stratton, S.C.

Martin, A.M., P.M.O. Owende, N.M. Holden, S.M. Ward, and M.J. O'Mahony, Designation of Timber Extraction Routes in a GIS Using Road Maintenance Cost Data, 10:32-38 (No. 9157).

McGinnis, G.D., see Wang, X.

Meil, J., see Bowyer, J.

Michael, J.H., Perceived Obligations of Future Forest Industry Employees: A Psychological Contracts Perspective, 10:39-46 (No. 9170).

Milota, M., see Bowyer, J.

Miner, R.A., see Stratton, S.C.

Monroe, P.A., see Chavez, A.

Morrell, J.J., C.M. Freitag, and C. Eddington, Effect of Preservative Treatment on Survival of Fungi in Western Red Cedar Utility Poles, 9:69-72 (No. 9155).

Morrell, J.J., P.F. Schneider, and R.S. Williams, Protecting Wood Decks From Biodegradation and Weathering: Evaluation of Deck Finish Systems, 11/12:27-32 (No. 9145).

Muehl, J., see Clausen, C.A.

Muehl, J.H., see Krzysik, A.M.

Munn, I.A., see Cox, B.M.

N

Nakajima, S., see Lam, F.

Ni, C., see Chui, Y.H.

Nicholas, D. see Vasishth, P.

Nogi, M., M. Yoshida, H. Yamamoto, and T. Okuyama, Reduction of Residual Stress in Logs by Direct Heat Treatment: Temperature Distribution Within the Furnace, 3:69-74, (No. 9039).

O

Octeau, P., see Gilbert, R.

Okuyama, T., see Nogi, M.

O'Mahony, M.J., see Martin, A.M.

Owende, P.M.O., see Martin, A.M.

P

Payne, C., S. Woodward, and J.A. Petty, Modification of the Growth Habit of the Softwood Disfiguring Fungus *Ophiostoma piceae* by Monoterpene Vapors, 7/8:89-92 (No. 9237).

Pendleton, D., see Shi, S.Q.

Peralta, P.N., see Gillis, C.M.

Petty, J.A., see Payne, C.

Price, E.W., see Shupe, T.E.

Q

Quin, F., see Zhang, J.

R

Raymond, S., see Barry, A.

Richter, D., see Verhey, S.

Ritter, M., see Burdock, E.

Ross, R.J., see Wang, X.

Ruddick, J.N.R., see Fang, F.

S

Salcudean, M., see Hua, L.

Sasaki, Y., see Ayarkwa, J.

Schajer, G.S., Lumber Strength Grading Using X-Ray Scanning, 1:43-50 (No. 9075).

Schmidt, E.L. and C. Westberg, Heartwood Temperatures of Red Pine Pole Stock During Pentachlorophenol Pressure Treatment and Presence of Decay Fungi Prior to Treatment, 11/12:41-44 (No. 9176).

Schmidt, E.L., D.L. Cassens, and B.A. Jordan, Control of Graystain in Yellow-Poplar Lumber by Log Fumigation With Sulfuryl Fluoride, 9:50-52 (No. 9149).

Schmidt, E.L., B. Kreber, and S. Boon, Fumigation of Red Beech Logs for Reducing Gray Stain in Lumber, 5:89-91 (No. 9132).

Schneider, P.F., see Morrell, J.J.

Schuler, A., R. Taylor, and P. Araman, Competitiveness of U.S. Wood Furniture Manufacturers, 7/8:14-20 (No. 9244).

Sellers, Jr., T., Wood Adhesive Innovations and Applications in North America, 6:12-22 (No. 9243).

Serrano, R. and D. Cassens, Reducing Warp and Checking in Plantation-Grown Yellow-Poplar 4 by 4's by Reversing Part Positions and Gluing in the Green Condition, 11/12: 37-40 (No. 9231).

Shi, S.Q., D.J. Gardner, D. Pendleton, and T. Hoffard, Timber Production From Reclaimed Creosote-Treated Wood Pilings: Economic Analysis and Quality Evaluation, 11/12:45-50 (No. 9193).

Shiau, R.-J., R.L. Smith, and E.T. Cesa, Role of Intermediaries in Technology Transfer in the Logging Industry: A Case Study With Portable Timber Bridges, 5:17-24 (No. 9034).

Shmulsky, R., Proportional Surface Drying of Small Loblolly Pine Cubes at 120°C, 4:90-92 (No. 9126).

Shmulsky, R. and H. Castillo, Accelerated Kiln Schedules for Drying of Hackberry, Red Oak, and Sweetgum Lumber, 11/12: 33-36 (No. 9273).

Shmulsky, R. and F.W. Taylor, Evalution of Energy Conservation by Second-Stage Drying, 3:75-78 (No. 9125).

Shook, S.R., and I.L. Eastin, A Characterization of the U.S. Residential Deck Material Market, 4:28-36 (No. 9118).

Shook, S.R., Y. Zhang, and F.G. Wagner, Wood Products Cooperatives: Overview and Exploratory Analysis, 3:25-33 (No. 9114).

Shook, S.R., see Eastin, I.L.

Shupe, T.F., C.Y. Hse, and E.W. Price, Flake Orientation Effects on Physical and Mechanical Properties of Sweetgum Flakeboard, 9:38-43 (No. 9138).

Shupe, T.F., C.Y. Hse, and E.W. Price, Technical Feasibility of Structural Flakeboard Made From Mixed Hardwoods and Cypress From Northern Florida, 1:62-64 (No. 9085).

Shupe, T.F., S.T. Lebow, E.T. Choong, and M. Xiong, Inadequate Redrying Linked to Dimensional Instability of CCA-Treated Southern Pine Lumber, 5:59-62 (No. 9130).

Shupe, T.F., see Chavez, A.

Simpson, I. and T. Haslett, Assessment of Comercial In-Line Meters for Measuring the Moisture Content of Radiata Pine Lumber, 3:65-68 (No. 9112).

Simpson, W.T. and C.A. Hart, Method for Esimating Air-Drying Times of Lumber, 11/12:56-63 (No. 9197).

Simpson, W.T. and X. Wang, Relationship Between Longitudinal Stress Wave Transit Time and Moisture Content of Lumber During Kiln-Drying, 10:51-54 (No. 9282).

Siry, J.P., F.W. Cubbage, and A.J. Malmquist, Potential Impacts of Increased Management Intensities on Planted Pine Growth and Yield and Timber Supply Modeling in the South, 3:42-48 (No. 9076).

Slahor, J.J., C.C. Hassler, and B. Dawson-Andoh, The Durability of Yellow-Poplar and American Beech Treated With Chromated Copper Arsenate, 4:62-66 (No. 9154).

Slahor, J.J., C.C. Hassler, and B. Dawson-Andoh, The Durability of Yellow-Poplar and Red Maple Treated With ACQ-B, 9:59-62 (No. 9250).

Slahor, J.J., H.M. Barnes, B. Dawson-Andoh, T.L. Amburgey, and C.C. Hassler, Durability of Yellow-Poplar and American Beech Treated With Creosote and Borate, 7/8:51-55 (No. 9248).

Smith, P.M., K. Hama, and T.M. Smith, Japanese Attendee Objectives for Building Products Trade Shows: A Cross-National Comparison, 11/12:78-83 (No. 9199).

Smith, R.L., see Bowe, S.A.

Smith, R.L., see Cumbo, D.W.

Smith, R.L., see Shiau, R.-J.

Smith, T.M., see Smith, P.M.

Song, X.M. and J.-Y. Hwang, Mechanical Properties of Composites Made With Wood Fiber and Recycled Tire Rubber, 5:45-51 (No. 8549).

Spelter, H., Efficacy of Curtailment Announcements as a Predictor of Lumber Supply, 7/8:44-46 (No. 9238).

Stephens, W.C., see Gillis, C.M.

Stern, E.G., Construction With Small-Diameter Roundwood, 4:71-82 (No. 9097).

Stockmann, V.E., see Bowyer, J.L.

Stratton, S.C., R.A. Miner, D.H. Word, E.H. Mannisto, and H.I. Mannisto, Estimated U.S. Forest and Paper Industry CO_2 Emissions Resulting From Compliance With Federal Environmental Regulations, 5:25-31 (No. 9110).

Su, W., see Conners, T.E.

Sun, C., see Zhang, D.

T

Tackett, B., see Zhang, J.

Tainter, F.H., see Xu, Z.

Taylor, A., P.A. Cooper, and Y.T. Ung, Effects of Deck Washes and Brighteners on the Leaching of CCA Components, 2:69-72 (No. 9099).

Taylor, A., see Chui, Y.H.

Taylor, J.L., see Cooper, P.A.

Taylor, F.W., see Shmulsky, R.

Taylor, R., see Schuler, A.

Templeton, M.C., see Conners, T.E.

Todoroki, C.L., Volume and Value Variation With Opening Face Position: An Investigation With Pruned Softwood Logs, 1:36-42 (No. 9087).

Trusty, W., see Bowyer, J.

U

Underwood, C.R., F.E. Woeste, J.D. Dolan, and S.M. Holzer, Permanent Bracing Design for MPC Wood Roof Truss Webs and Chords, 7/8:73-81 (No. 9128).

Ung, Y.T., see Cooper, P.A.

Ung, Y.T., see Taylor, A.

Unsal, O., see Yilgor, N.

V

Van der Waals, J., see Kreber, B.

Vasishth, P., and D. Nicholas, Effect of Polyvinyl Pyrrolidone on the Dimensional Stability and Leachability of Copper From Wood Treated With Ammoniacal Copper Formulations, 1:51-54 (No. 9077).

Velupillai, L., see Chavez, A.

Verhey, S., P. Laks, and D. Richter, Laboratory Decay Resistance of Woodfiber/Thermoplastic Composites, 9:44-49 (No. 9160).

Via, B.K., A. Zink-Sharp, F. Woeste, and J.D. Dolan, Influence of Specific Gravity on Embedment Gaps in Metal-Plate-Connected Truss Joints, 10:88-92 (No. 9218).

Vlosky, D.A., see Chavez, A.

Vlosky, R.P. and N.P. Chance, Employment Structure and Training Needs in the Louisiana Value-Added Wood Products Industry, 3:34-41 (No. 9119).

Vlosky, R.P. and Q. Wu, A Brief Look at Raw Material Usage in the Furniture and Cabinet Industries in the Southern United States, 9:25-29 (No. 9251).

Vlosky, R.P., see Chavez, A.

Vlosky, R.P., see Humphries, S.

Vos, D.J., see Falk, R.H.

W

Wagner, F.G., see Shook, S.R.

Wakeling, R., see Kreber, B.

Wang, X., R.J. Ross, J.R. Erickson, J.W. Forsman, G.D. McGinnis, and, R.C. De Groot, Nondestructive Evaluation of Potential Quality of Creosote-Treated Piles Removed From Service, 2:63-68 (No. 9092).

Wang, X., see Simpson, W.T.

Ward, S.M., see Martin, A.M.

West, C., see Bowyer, J.

Westberg, C., see Schmidt, E.L.

White, M.S., see Clarke, J.W.

Williams, R.S., see Morrell, J.J.

Willis III, D.B., see Carino, H.F.

Wilson, J., see Bowyer, J.

Winandy, J.E., Thermal Degradation of Fire-Retardant-Treated Wood: Predicting Residual Service Life, 2:47-54 (No. 9095).

Winistorfer, P., see Bowyer, J.

Winistorfer, P.M., see Andrews, C.K.

Winistorfer, P.M., see Young, T.M.

Woeste, F., see Via, B.K.

Woeste, F.E., see Underwood, C.R.

Woodward, S., see Payne, C.

Word, D.H., see Stratton, S.C.

Wu, Q., see Vlosky, R.P.

X

Xiong, M., see Shupe, T.F.

Xu, Z., T.D. Leininger, A.W.C. Lee, and F.H. Tainter, Physical, Mechanical, and Drying Properties Associated With Bacterial Wetwood in Red Oaks, 3:79-84 (No. 9086).

Y

Yamamoto, H., see Nogi, M.

Yan, H., see Conners, T.E.

Yang, D.-Q., A Method for the Prevention of Wood Decay From Nail Penetration, 4:67-70 (No. 9115).

Yang, D.-Q., Staining Ability of Various Sapstaining Fungi on Jack Pine Short Log Sections, 2:73-76 (No. 9094).

Yang, D.-Q. and R. Beauregard, Check Development on Jack Pine Logs in Eastern Canada, 10:63-65 (No. 9281).

Yilgor, N., O. Unsal, and S.N. Kartal, Physical, Mechanical, and Chemical Properties of Steamed Beech Wood, 11/12:89-93 (No. 9183).

Yoshida, M., see Nogi, M.

Young, T.M. and P.M. Winistorfer, The Effects of Autocorrelation on Real-Time Statistical Process Control With Solutions for Forest Products Manufacturers, 11/12:70-77 (No. 9191).

Youngquist, J.A., see Krzysik, A.M.

Youngquist, J.A., see Youngs, R.L.

Youngs, R.L. and A.L. Hammett, Diversity, Productivity, Profitability, Sustainability, and the Tao of Underutilized Species, 1:29-35 (No. 9068).

Youngs, R.L. and J.A. Youngquist, Forest Products Research and IUFRO History and Potential, 2:12-19 (No. 9240).

Z

Zhang, D. and C. Sun, U.S. - Canada Softwood Lumber Trade Disputes and Lumber Price Volatility, 4:21-27 (No. 9207).

Zhang, J., D.E. Lyon, F. Quin, and B. Tackett, Bending Strength of Gusset-Plate Joints Constructed of Wood Composites, 5:40-44 (No. 9135).

Zhang, J., F. Quin, and B. Tackett, Bending Fatigue Life of Two-Pin Dowel Joints Constructed of Wood and Wood Composites, 10:73-78 (No. 9184).

Zhang, J., F. Quin, and B. Tackett, Bending Strength and Stiffness of Two-Pin Dowel Joints Constructed of Wood and Wood Composites, 2:29-35 (No. 9101).

Zhang, X., see Hartsough, B.R.

Zhang, Y., see Shook, S.R.

Zink-Sharp, A., see Via, B.K.

Zui, H., see Eckelman, C.

Statement of Ownership, Management, and Circulation
(Act of August 12, 1970; Section 3685, Title 39, United States Code)

1. Date of filing: October 8, 2001.
2. Title of publication: *FOREST PRODUCTS JOURNAL*.
3. Frequency of issue: 10 times a year.
4. Location of known office of publication: 2801 Marshall Court, Madison, Wi 53705.
5. Location of the headquarters or general business offices of the publishers: Same.
6. Names and addresses of publisher and editor: Publisher, Forest Products Society - A.B. Brauner, Executive Vice President and Treasurer, 2801 Marshall Court, Madison, WI 53705; Editor, Erin Bosch, same address.
7. Owner, name and address: Forest Products Society, 2801 Marshall Court, Madison, WI 53705.
8. Known bondholders, mortgages, and other security holders owning or holding 1% or more of total amount of bonds, mortgages, or other securities: None.
9. The purpose, function, and nonprofit status of this organization and the exempt status for Federal income tax purposes have not changed during the preceding 12 months.
10. Extent and nature of circulation:

	Average No. of Copies Each Issue During Preceding 12 Months	No. of Copies of Single Issue Nearest Filing Date
A. Total no. of copies printed (net press run)	2875	2800
B. Paid circulation:		
1. Sales through dealers and carriers, street vendors, and counter sales	496	501
2. Mail subscriptions	1919	1920
C. Total paid circulation	2415	2421
D. Free distribution	118	118
E. Total distribution (sum of C and D)	2533	2539
F. Office use, left-over, unaccounted, spoiled after printing	342	261
G. Total (sum of E and F, should equal net press run in A)	2875	2800
H. Percent paid and/or requested circulation	95.3%	95.4%

I certify that the statements made by me are correct and complete.
A.B. Brauner, Executive Vice President and Treasurer